SPECS



Solar Series Permanent Elevated Helipad S188 LED Wind Cone

With over 50 years experience in the design, manufacture and delivery of internally lighted wind cones, the Solar Series Permanent Elevated Helipad S188 LED Wind Cone is the most proven and most installed off grid solution in the market. Operating on all continents in the most demanding environments, industry's toughest clients rely on the Solar Series Permanent Elevated Helipad S188 LED Wind Cones for civil and defense operations. Backed by the best warranty in the industry. Aviation Renewables provide both standard and custom designed solar LED wind cone solutions for airports, runways, helipads and manufacturing facilities.

The Solar Series Permanent Elevated Helipad S188 Wind Cone includes intelligently engineered aluminum tilt-pole with a patented aluminum swivel system that is designed to facilitate easy installation and servicing by a single person with no electrical infrastructure requirements. Unlike many competing manufacturers that require two concrete pads the integrated tower and power system of the Solar Series S188 only requires one mounting point saving time and cost.







Web: www.aviationrenewables.com Email: arc@aviationrenewables.com Phone: +1 (250) 590 1272

SPECS

Solar Series Permanent Elevated Helipad SS188 LED Wind Cone

FEATURE BENEFITS

INCREASE SAFETY & VISIBILITY

Internally lighted windsocks are more visible for pilots than externally lighted. The Solar Series wind socks are made with a durable but lightweight colourfast fabric.

REDUCE COSTS

Being 100% solar powered and self-contained, single mounting point installation is dramatically less expensive compared to competitors with detached solar systems that require 2 mounting points (one for tower, one for power system) or conventional systems that require trenching, cabling or electrical services. No power requirements: no reliance on grid or generator power.

REDUCE MAINTENANCE

Solar powered means no external power and zero energy costs. Internal LED lighting is up to 10 times more energy efficient than external incandescent windsock lighting.

FEATURING

All aluminum construction with stainless steel hardware. Patented fully sealed swivel complete with high quality bearings. Vivid internally lit fixture providing precisely directed illumination. Tilt mechanism for easy installation with one or two people.



SPECIFICATIONS

COMPLIANCE

Elevated Helipad	ICAO for Elevated Heliports Annex 14, Vol 2, 5.1.1.
S188 Series	and FAA for Elevated Heliports F806 Size 1

OPTICAL

OTTIONE	
Obstruction Light	3 Options: No Light, Visible FAA L810 (ICAO LIOL), Visible L810 with IR
Sock Lighting	12W cool white LED floodlight luminaire
Output	580 lumens at source
Configuration	Internally lit, adjustable LED intensity
Operation Profile	Dusk to dawn or Radio Control
LED Life Expectancy	Up to 60,000 hours

MECHANICAL

Configuration	Aluminum tilt pole
Overall Height	17'9" standard, custom heights available
Tilt Mechanism	Counterbalanced tilt at 4'6"
Swivel	Patented maintenance free sealed aluminum swivel
Mounting	Aluminum base plate with 4-bolt pattern for concrete mount. 3/4 hot dipped galvanized anchor bolts
Frangibility	Optional ICAO and FAA certified frangible fuse bolt mounting system
Sock Dimensions	18" x 8'
Fabric	Polyethylene coated colorfast 4.5oz nylon Orange/White, Solid Orange or custom
Frame Material	All Aluminum

ELECTRICAL

Configuration	Integrated DC solar charging system
Solar Module	100 Watt poly-crystalline panel
Battery	100 Ahr AGM sealed battery approved for air transport
Charge Controller	Sealed precision micro controller with push to test button
Autonomy	5 days or greater, depending on location
RF Controller	Optional Radio Frequency Controller for on/off control
WARRANTY	

Warranty 3 year warranty. Excludes battery and fabric

Web: www.aviationrenewables.com Email: arc@aviationrenewables.com Phone: +1 (250) 590 1272