



Q-Aviation Lighting / Heliport Lighting / Q-Beacon-Lights

Q-BEACON LIGHT



TECHNICAL DETAILS

Application:	Helipad/ heliport
Light Colour:	White
Flash rate:	Morse "H"
Light Source:	LED
Light Intensity:	1.500 cd
Input Voltage:	From controller
Vertical Beam Profile:	As per ICAO
Colour chromaticity:	As per ICAO, 6000K
Enclosure:	Aluminium, powder coated
Cable Glands:	1 x M25 x1.5
Mounting:	Rigid
Ambient Temp:	-25° to +65° C
In compliance with:	ICAO annex 14, Volume II
Cable size:	9-17mm
Consumption:	100 Watt
Life expectancy:	100.000+ hours
IP index:	IP 67
Weight:	3.3 kg
Dimensions:	163x177x150 mm (LxWxH)
Packaging dimension:	250x250x250 mm (LxWxH)

CERTIFICATES




DESCRIPTION

The Q-Beacon Light system indicates the location of the, heliport or Helipad. The lighting system is dimmable to avoid dazzling during the final stages of the approach and landing.

The heliport beacon is emitting repeated series of equispaced short duration white flashes in the format of the morse letter 'H'.

ORDER CODE

Q13RI03 – Q-Beacon Light



MAIN DIMENSIONS

Find the main dimensions and mounting dimensions in the image below

