



Q-Aviation Lighting / Helipad Lighting / Q-Flushmount Approach Light (FATO)

Q-FLUSHMOUNT APPROACH LIGHT (FATO) TECHNICAL DETAILS



Application:	Helipad/Heliport
Classification:	Safe Area
Light Source:	LED, steady burning
Light Colour:	White, 6000K
Light Intensity:	55 cd
Vertical Beam Profile:	as per ICAO
Colour chromaticity:	as per ICAO
Enclosure:	Aluminium, Powder coated
Mounting:	Flushmount, 4x M6
Input Voltage:	1) 100-240 Vac, 50-60 Hz 2) 24 Vdc
External Earthing:	up to 4mm ²
Ambient Temp:	-25° to +65° C
In Compliance With:	ICAO, Annex 14 vol 2
Cable glands included:	2 x M25x1.5
Cable Outer Dimensions:	11 - 19mm
Consumption:	8 Watt
Life expectancy:	100.000+ hours
IP index:	IP 67
Weight:	2.20 kg.
Dimensions:	200x200x122 mm (LxWxH)
Packaging dimension:	250x250x150 mm (LxWxH)

DESCRIPTION

The Q-Flushmount Helipad Approach Light is an ICAO compliance 55 cd approach light for all Helipad and Heliport facilities where flush installation is preferred. The Q-Flushmount Approach Light is available in several configurations such as 100-240 Vac and 24 Vdc.

CERTIFICATES



ORDER CODE

Q22FM03 – Q-Flushmount Approach Light (FATO)

Q22FM03 **11** **R1**

- 11** Input power: 100-240 Vac
- 12** Input power: 24 Vdc



MAIN DIMENSIONS

Find the main dimensions and mounting dimensions in the image below

