



Q-Aviation Lighting / Helipad Lighting / Flushmount Perimeter Light

Q-FLUSHMOUNT PERIMETER LIGHT



TECHNICAL DETAILS

Application:	Helipad/Heliport
Light Colour:	Green, steady burning
Light Source:	LED
Light Intensity:	50 cd
Vertical Beam Profile:	as per ICAO
Colour chromaticity:	as per ICAO, 530nm
Enclosure:	Aluminium, Powder coated
Mounting:	Flushmount, 4x M6
Input Voltage:	1) 100-240 Vac 50/60Hz 2) 24 Vdc
External Earthing:	up to 4mm ²
Ambient Temp:	-25° to +65° C
In Compliance With:	ICAO Annex 14 Vol 2.
Cable bottom entry:	2 x M25x1.5
Cable glands included:	2 x M25x1.5
Cable size:	9-17mm
Consumption:	8 Watt
Life expectancy:	100.000+ hours
IP index:	IP 67
Weight:	2.20 kg.
Dimensions:	200x200x122 mm (LxWxH)
Packaging dimension:	250x250x150 mm (LxWxH)

CERTIFICATES



DESCRIPTION

The Q-Flushmount Helipad Perimeter Light is an ICAO compliance 50 cd perimeter light for all Helipad and Heliport facilities where flush installation is preferred. The Q-Flushmount Helipad Perimeter Light is available in several configurations such as 100-240 Vac and 24 Vdc.

ORDER CODE

Q10FM03 11 R1

Q10FM03 – Flushmount Perimeter Light

- 11** Input power: 100-240 Vac
- 12** Input power: 24 Vdc



MAIN DIMENSIONS

Find the main dimensions and mounting dimensions in the image below

