



Q-Aviation Lighting / Helideck Lighting / Q-Helipad Floodlight

## Q-HELIPAD FLOODLIGHT

## TECHNICAL DETAILS



Application:	Helipad/ Heliport
Classification:	Safe Area
Light Source:	LED, steady burning
Light Colour:	White 5.700K
Light Intensity:	5.000 cd
Vertical Beam Profile:	as per CAP437/ICAO
Colour chromaticity:	as per CAP437/ICAO, 5.700K
Enclosure:	Aluminium, Powder coated
Mounting:	Rigid, 4 x M8
Input Voltage:	1) 100-240 Vac 50-60 Hz 2) 24 Vdc
External Earthing:	up to 4mm2
Ambient Temp:	-25° to +65° C
In Compliance With:	CAP437/ICAO
Cable glands included:	2x M25x1.5
Cable stops included:	1 x M25x1.5
Cable Outer Dimensions:	11,1 – 20,0mm
Consumption:	6 Watt
Life expectancy:	100.000+ hours
IP index:	IP 67
Weight:	2.90 kg
Dimensions:	265x180x186 mm (LxWxH)
Packaging dimension:	300x200x200 mm (LxWxH)

## CERTIFICATES



## DESCRIPTION

The Q-Floodlight is a CAP437 compliance 5.000 cd floodlight for Safe Area. The Q-Floodlight is available in several configurations such as 100-240 Vac and 24 Vdc.

## ORDER CODE

**Q12FR03 11 R1**

**Q12FR03** – Q-Helipad Floodlight

- 11** Input power: 100-240 Vac
- 12** Input power: 24 Vdc

**MAIN DIMENSIONS**

The main dimensions and mounting are displayed dimensions in the image below:

